

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
YALE MANUFACTURER	ERC100HH	2013	A938N01693L

Mast		Hours	1195
Mast Height Lowered	85	Voltage	48 Volt
Mast Height Raised	110.2	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	Monotrol
Capacity	10000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition	Bars Missing	Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition	Missing	Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	60
Overhead Guard Comments		Drive Tires Condition	
Seat Condition		Steer Tires % Remaining	60
Seat Comments		Steer Tires Condition	
General Appearance Condition		Steer Axle Condition	
General Appearance Comments		Steer Axle Comments	
		Brakes Condition	Soft
		Brakes Comments	Out of Adjustment

General Comments

Missing mat

Battery Present	Yes
Charger Present	Yes

Electrical Condition	
Electrical Comments	

Inspector Company Name	Bill Valaitis	Inspection Date	12/20/2018 12:45:50 PM
Inspector Name	bvalaitis		

(* Legend: =Checked OK)

Yale

Lift Truck Model ERC100VHN48TV085

Serial No. A938N01693L

Attachment: 1219 mm (48 in) Carriage + Bruce Industrial Co. False carriage
w/6 Forks 1980 FRK-6

Truck Wt. Less Battery 6260 kg (13800 lb) Type EO 48 Volts

Truck Wt. Max Battery 8780 kg (19350 lb) Max A.H. (6 Hr Rt) 1600

Allowable Battery Wt: 1810 kg (4000 lb) to 2520 kg (5550 lb)

Tread Width 1020 mm (40.0 in) Back Tilt 5.0 Degrees

Tire Front

Rear

Size 22X12X16 Cushion

18X7X12-1/8 Cushion

Pressure

MAXIMUM CAPACITY	Load Height	Load Center	
	Dim. A	Dim. B	Dim. C
4240 kg (9350 lb)	2800mm (110.2 in)	610 mm (24 in)	610 mm (24 in)
0 kg (0 lb)	0 mm (0 in)	0 mm (0 in)	0 mm (0 in)



104 1928 4









