

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E30HSD2	2012	B219N01984K

Mast	3 Stage FFL (Triplex)	Hours	2068
Mast Height Lowered	83	Voltage	36 Volt
Mast Height Raised	192	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	3000	Tires	

Mast Condition	Steering Pump Condition		
Mast Comments	Steering Pump Comments		
Lift Cylinder Condition	Hydraulic Pump Condition		
Lift Cylinder Comments	Hydraulic Pump Comments		
Tilt Cylinder Condition	Hydraulic Motor Condition		
Tilt Cylinder Comments	Hydraulic Motor Comments		
Carriage Condition	Control System Condition		
Carriage Comments	Control System Comments		
Load Backrest Condition			
Load Backrest Comments	Drive Motor Condition		
Forks Condition	Drive Motor Comments		
Forks Comments	Differential Condition		
	Differential Comments		
Overhead Guard Condition	Drive Tires % Remaining	10	
Overhead Guard Comments	Drive Tires Condition	Chunked	
	Steer Tires % Remaining	10	
Seat Condition	Steer Tires Condition	Chunked	
Seat Comments	Steer Axle Condition		
	Steer Axle Comments		
General Appearance Condition	Brakes Condition		
General Appearance Comments	Brakes Comments		
General Comments	Battery Present	Yes	
Left light out. Truck is very rusted all over. All Tires chunked and worn.	Charger Present	No	
	Electrical Condition	Lights inoperable	
	Electrical Comments		

Inspector Company Name	Hilo Equipment & Services	Inspection Date	7/26/2018 2:32:27 PM
Inspector Name	jbird		

(* Legend: =Checked OK)











WARNING

Trained Operators and Mechanics Only



Read Operating Manual located on seat or in operators compartment

Failure to follow operating, inspection, and maintenance instructions can cause serious injury or death!
CAPACITY WITH MAST VERTICAL AND EQUIPPED AS SHOWN



Lift Truck Model E30HSD2-16

Serial No. B219N01984K

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2940 kg (6480 lb) Type E 36 Volts
Truck Wt. Max Battery 3990 kg (8780 lb) Max A.H. (6 ft Rf) 1240
Allowable Battery Wt. 850 kg (1880 lb) to 1040 kg (2300 lb)
Tread Width 490 mm (35 in) Back Tilt 5 Degrees

Tire Size Front 18X7X12-16 Cushion Rear 10.60X5X6.5 Poly 92 Duro
Pressure ---

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1290 kg (2850 lb)	4900mm (192.9 in)	610 mm (24 in)	610 mm (24 in)
kg (lb)	mm (in)	mm (in)	mm (in)



1 2940

