

# CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E50XN	2013	A268N10266L

Mast	3 Stage FFL (Triplex)	Hours	6404
Mast Height Lowered		Voltage	36 Volt
Mast Height Raised	189	Attachment	Side Shifter
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity		Tires	Cushion

Mast Condition	Steering Pump Condition	
Mast Comments	Steering Pump Comments	
Lift Cylinder Condition	Hydraulic Pump Condition	
Lift Cylinder Comments	Hydraulic Pump Comments	
Tilt Cylinder Condition	Hydraulic Motor Condition	
Tilt Cylinder Comments	Hydraulic Motor Comments	
Carriage Condition	Control System Condition	
Carriage Comments	Control System Comments	
Load Backrest Condition	Drive Motor Condition	
Load Backrest Comments	Drive Motor Comments	
Forks Condition	Differential Condition	
Forks Comments	Differential Comments	
Overhead Guard Condition	Drive Tires % Remaining	80
Overhead Guard Comments	Drive Tires Condition	
Seat Condition	Steer Tires % Remaining	80
Seat Comments	Steer Tires Condition	
General Appearance Condition	Steer Axle Condition	
General Appearance Comments	Steer Axle Comments	
	Brakes Condition	
	Brakes Comments	

## General Comments

Battery is in very poor condition

Battery Present	Yes
Charger Present	Yes
Electrical Condition	
Electrical Comments	

Inspector Company Name	Pape	Inspection Date	12/17/2018 3:00:58 PM
Inspector Name	bemerson		

(\* Legend: =Checked OK)

# WARNING

Operators and  
Mechanics Only

Read Operating  
Manual located on  
seat or in  
operators  
compartment

to follow operating  
tion, and maintenance  
ctions can cause  
us injury or death.

**CAPACITY WITH MAST  
VERTICAL AND  
EQUIPPED AS SHOWN**



Lift Truck Model E50XN-27

Serial No. A268N10266L

Attachment: 978 mm (39 in) SS Crg + 1220 mm (48 in) Forks

Truck Wt. Less Battery 3370 kg (7430 lb) Type E 36 Volts

Truck Wt. Max Battery 4870 kg (10720 lb) Max A.H. (6 Hr RE) 1400

Allowable Battery Wt. 1040 kg (2300 lb) to 1500 kg (3300 lb)

Tread Width 890 mm (35.2 in) Back Tilt 5 Degrees

Tire Front

Rear

Size 21X7X15 Cushion

16X6X10.5 Cushion

Pressure

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
2110 kg (4650 lb)	4800 mm (189 in)	610 mm (24 in)	610 mm (24 in)
2180 kg (4800 lb)	4350 mm (171.3 in)	610 mm (24 in)	610 mm (24 in)









Type **018085F23**  
6 Hour Capacity **935 A.H.**  
Nominal Voltage **36**  
Finish Rate **47 Amps**  
Specific Gravity **1275-1285**

Battery Weight Stamped on Tray

Give serial number on connector when reordering.

 **HAWKER**  
P.O. Box 808  
2717 - Charlotte, N.C. 28217  
Charlotte, Tennessee 37133  
800-226-9008 - Fax 800-410-4291

Battery I.D.# **PL103180309**



- E-583 Battery with cover
- EO-583 Battery without cover
- EE-583 Battery (sparkproof)

AS TO FIRE AND ELECTRIC  
SHOCK HAZARD ONLY  
STORAGE BATTERY TYPE FOR  
USE IN INDUSTRIAL TRUCKS  
1273

EO

