

# CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E30XN	2013	A269N02194L

Mast	3 Stage FFL (Triplex)	Hours	6154
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	
Capacity	3000	Tires	Cushion

Mast Condition	Steering Pump Condition
Mast Comments	Steering Pump Comments
Lift Cylinder Condition	Hydraulic Pump Condition
Lift Cylinder Comments	Hydraulic Pump Comments
Tilt Cylinder Condition	Hydraulic Motor Condition
Tilt Cylinder Comments	Hydraulic Motor Comments
Carriage Condition	Control System Condition
Carriage Comments	Control System Comments
Load Backrest Condition	
Load Backrest Comments	Drive Motor Condition
Forks Condition	Drive Motor Comments
Forks Comments	Differential Condition
	Differential Comments

Overhead Guard Condition	Drive Tires % Remaining	30
Overhead Guard Comments	Drive Tires Condition	

Seat Condition	Damaged	Steer Tires % Remaining	30
Seat Comments	cushion needs replacement	Steer Tires Condition	

General Appearance Condition	Steer Axle Condition
General Appearance Comments	Steer Axle Comments
	Brakes Condition
	Brakes Comments

General Comments	Battery Present	Yes
	Charger Present	No

1. Right tail light needs replacement  
2. All tires need replacement, low on tread.

Electrical Condition
Electrical Comments

Inspector Company Name	Johnny Holguion	Inspection Date	11/25/2018 5:25:26 PM
Inspector Name	szuege		

(\* Legend: =Checked OK)

# WARNING

Operators and  
Others Only



Lift Truck Model E30XN  
Serial No. A269N02194L

Attachment: 907 mm (36 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2550 kg (5610 lb) Type EO 36 Volts  
Truck Wt. Max Battery 3680 kg (8110 lb) Max A.H.(6 Hr R0)1200  
Allowable Battery Wt. 840 kg (1850 lb) to 1130 kg (2500 lb)  
Tread Width 800 mm (31.8 in) Back Tilt 5 Degrees

Type Front Rear  
Size 18RX12-1/8 Cushion 15X5X11-1/4 Cushion  
Pressure \_\_\_\_\_

MAXIMUM CAPACITY	Load Height	Load Center	
	Dim. A	Dim. B	Dim. C
1270 kg (2800 lb)	4750mm (187 in)	610 mm (24 in)	610 mm (24 in)
1350 kg (2980 lb)	4300 mm (169.3 in)	610 mm (24 in)	610 mm (24 in)















