## **CONDITION REPORT - ELECTRIC**

Manufacturer	Model	Year	Serial Number A268N10268L		
HYSTER COMPANY	E50XN	2013			
Mast	3 Stage FFL (Triplex)		Hours	6498	
Mast Height Lowered			Voltage	36 Volt	
Mast Height Raised	189		Attachment	Side Shifter	
Hydraulic Control Valve	3-Function		Directional Control	Lever	
Capacity			Tires	Cushion	
Mast Condition			Steering Pump Condition		
Mast Comments			Steering Pump Comments		
Lift Cylinder Condition			Hydraulic Pump Condition		
Lift Cylinder Comments			Hydraulic Pump Comments		
Tilt Cylinder Condition			Hydraulic Motor Condition		
Tilt Cylinder Comments			Hydraulic Motor Comments		
Carriage Condition			Control System Condition		
Carriage Comments			Control System Comments		
Load Backrest Condition					
Load Backrest Comments			Drive Motor Condition		
Forks Condition			Drive Motor Comments		
Forks Comments			Differential Condition		
			Differential Comments		
Overhead Guard Condition			Drive Tires % Remaining	70	
Overhead Guard Comments			Drive Tires Condition		
			Steer Tires % Remaining	70	
Seat Condition			Steer Tires Condition		
Seat Comments			Steer Axle Condition		
			Steer Axle Comments		
General Appearance Condition			Brakes Condition		
General Appearance Comments			Brakes Comments		
General Comments			Battery Present	Yes	
			Charger Present	Yes	
			Electrical Condition		
			Electrical Comments		
			4		

Inspection Date

12/17/2018 3:01:37 PM

(\* Legend: =Checked OK)

Inspector Company Name

Inspector Name

Pape

bemerson

Lift Truck Model E50XN-27 Serial No. A268N10268L Attachment: 978 mm (39 in) SS Crg + 1262 mm (48 in) Forks and Truck Wt. Less Battery 3370 kg (7430 lb) Type E 36 Volts Truck Wt. Max Battery 4870 kg (10720 lb) Max A.H.(6 Hr Rt)1400 Allowable Battery Wt. 1040 kg (2300 lb) to 1500 kg (3300 lb) ting Tread Width 890 mm (35.2 in) Back Tilt 5 Degrees ted on Rear Front Tire 16X5X10.5 Cushion 21X7X15 Cushion Size nt Pressure Load Center Load Height rating. MAXIMUM Dim. C Dim. B itenance Dim. A CAPACITY 610 mm 610 mm se 4800mm (24 in) 2110 kg (24 in) ith! (189 in) (4650 lb) 610 mm H MAST 610 mm 4350 mm (24 in) (24 in) 2180 kg (171.3 in)

(4800 tb)

SHOWN





