

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
YALE MANUFACTURER	ERP030VT	2013	G807N04538L

Mast	3 Stage FFL (Triplex)	Hours	11221
Mast Height Lowered	6ft 10in	Voltage	36 Volt
Mast Height Raised		Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	3000lb	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition			
Load Backrest Comments		Drive Motor Condition	
Forks Condition		Drive Motor Comments	
Forks Comments		Differential Condition	
		Differential Comments	
Overhead Guard Condition	Damaged	Drive Tires % Remaining	10
Overhead Guard Comments	Impact damage Top	Drive Tires Condition	Flat
		Steer Tires % Remaining	0
Seat Condition	Damaged	Steer Tires Condition	Chunked
Seat Comments	Seat cushion has a tear	Steer Axle Condition	
		Steer Axle Comments	
General Appearance Condition	Fair	Brakes Condition	
General Appearance Comments	Sheet metal damage	Brakes Comments	
General Comments		Battery Present	Yes
		Charger Present	Yes
		Electrical Condition	
		Electrical Comments	

Inspector Company Name	Yale Chase	Inspection Date	8/29/2018 11:37:14 AM
Inspector Name	Greg Owens		

(* Legend: =Checked OK)

Yale

Lift Truck Model ERP030VTN36TE082

Serial No. G807N04538L

Attachment: 978 mm (39 in) Carriage + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2470 kg (5440 lb) Type E 36 Volts

Truck Wt. Max Battery 3470 kg (7640 lb) Max A.H. (6 Hr Rt) 880

Allowable Battery Wt. 770 kg (1700 lb) to 1000 kg (2200 lb)

Tread Width 880 mm (34.9 in) Back Tilt 5 Degrees

Tire

Front

Rear

NOTICE TO USER

U.S.A. Occupational Safety and Health
Federal safety codes

Full Solid











