

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	J40XNT	2013	K160N03332L

Mast	3 Stage FFL (Triplex)	Hours	5008
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	
Capacity	4000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	60
Overhead Guard Comments		Drive Tires Condition	Chunked
Seat Condition	Damaged	Steer Tires % Remaining	60
Seat Comments	Cushion needs replacement	Steer Tires Condition	
General Appearance Condition	Fair	Steer Axle Condition	
General Appearance Comments		Steer Axle Comments	
		Brakes Condition	
		Brakes Comments	

General Comments

1. Unusual noise when using tilt function
 2. Right rear tail light missing
 3. Strobe light unit needs replacing
 4. Rear worklight needs replacing
 5. Seat cushion needs replacing
 6. Drive tires chunked
 7. Currently using rental battery. Need to have leased battery fixed, more than likely some dead cells.

Battery Present	Yes
Charger Present	Yes
Electrical Condition	Dead / low battery
Electrical Comments	

Inspector Company Name	Johnny Holguin	Inspection Date	11/26/2018 10:38:16 AM
Inspector Name	szuege		

(* Legend: =Checked OK)



Lift Truck Model **J40XNT**

Serial No: **K160N03332L**

Attachment: 978 mm (39 in) SS Crg + 1220 mm (48 in) F

Truck Wt. Less Battery 2600 kg (5730 lb) Type

Truck Wt. Max Battery 3690 kg (8130 lb) Max A.

Allowable Battery Wt. 950 kg (2100 lb) to 1090 kg (2400 lb)

Tread Width 910 mm (35.8 in) Back Tilt 5 Degrees

Tire Size Front Rear
 Pressure 200/50-10 Solid 15X4.5-8/3.0 Dual

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1630 kg (3600 lb)	4750mm (156 in)	610 mm (24 in)	610 mm (24 in)
1660 kg (3660 lb)	4420 mm (174.2 in)	610 mm (24 in)	610 mm (24 in)













