

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
YALE MANUFACTURER	ERC100HH	2013	A938N01694L

Mast	2 Stage FFL (Duplex)	Hours	1294
Mast Height Lowered	85	Voltage	48 Volt
Mast Height Raised	110.3	Attachment	None
Hydraulic Control Valve		Directional Control	Monotrol
Capacity	10000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	

Load Backrest Condition	Bars Missing
Load Backrest Comments	
Forks Condition	Missing
Forks Comments	

Drive Motor Condition	
Drive Motor Comments	
Differential Condition	
Differential Comments	
Drive Tires % Remaining	70
Drive Tires Condition	
Steer Tires % Remaining	60
Steer Tires Condition	
Steer Axle Condition	
Steer Axle Comments	

Overhead Guard Condition
Overhead Guard Comments

Seat Condition
Seat Comments

General Appearance Condition
General Appearance Comments

General Comments

Lock on hood frozen Missing floor plates and mats. Hydraulic control latch not working

Battery Present	Yes
Charger Present	Yes
Electrical Condition	
Electrical Comments	

Inspector Company Name	Bill Valaitis	Inspection Date	12/14/2018 10:38:44 AM
Inspector Name	bvalaitis		

(* Legend: =Checked OK)

WARNING

Operators and
Mechanics Only

Read Operating
Manual located
on seat or in
operator's
compartment

Follow operating,
and maintenance
instructions. Failure
to do so can cause
injury or death!
OPERATE WITH MAST
RETRACTED AND
LOADS SECURED AS SHOWN

Yale

Lift Truck Model ERC100VHN48TV085

Serial No. A938N01694L

Attachment: 1219 mm (48 in) Carriage + Bruce Industrial Co. False carriage
w/5 Forks 1980 FRK-6

Truck Wt. Less Battery 6260 kg (13800 lb) Type EO 48-Volts
Truck Wt. Max Battery 8780 kg (19350 lb) Max A.H. (6 Hr Rt) 1600
Allowable Battery Wt. 1810 kg (4000 lb) to 2520 kg (5550 lb)
Tread Width 1020 mm (40.0 in) Back Tilt 5.0 Degrees
Tire Front Rear
Size 22X12X16 Cushion 18X7X12-1/8 Cushion
Pressure --

MAXIMUM CAPACITY	Load Height	Load Center	
	Dim. A	Dim. B	Dim. C
4240 kg (9350 lb)	2800mm (110.2 in)	610 mm (24 in)	610 mm (24 in)
0 kg (0 lb)	0 mm (0 in)	0 mm (0 in)	0 mm (0 in)









