

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	J30XNT	2013	K160N03317L

Mast	3 Stage FFL (Triplex)	Hours	5309
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	
Capacity	3000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	60
Overhead Guard Comments		Drive Tires Condition	Chunked
Seat Condition	Damaged	Steer Tires % Remaining	60
Seat Comments	Cushion needs replacement	Steer Tires Condition	
General Appearance Condition		Steer Axle Condition	
General Appearance Comments		Steer Axle Comments	
General Comments		Brakes Condition	
		Brakes Comments	
		Battery Present	Yes
		Charger Present	No
		Electrical Condition	
		Electrical Comments	

1. Backup Alarm needs replacing2. Seat Cushion needs replacing3. Strobe light needs replacing4. Drive tires chunked

Inspector Company Name	Johnny Holguin	Inspection Date	11/25/2018 5:34:58 PM
Inspector Name	szuege		

(* Legend: =Checked OK)











WARNING

Operators and
Technicians Only

Read Operating
Manual located on
operator's seat or in
operator's compartment
before operating.
Improper operation and
maintenance
can cause injury or death!
CAPACITY WITH MAST
EXTENDED AND
JUMPER AS SHOWN



Lift Truck Model J30XNT

Serial No. K160N03317L

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2370 kg (5220 lb) Type ED J6 Voles
Truck Wt. Max Battery 3510 kg (7720 lb) Max A 11 (9 1/8) 10 (8 1/8)
Allowable Battery Wt. 910 kg (2000 lb) to 1130 kg (2500 lb)
Tread Width 880 mm (34.9 in) Back Tilt 8 Degrees

Tire Size 18X7.5 Solid
Front 18X7.5 Solid
Rear 18X7.5 Solid

MAXIMUM CAPACITY	Load Height		Load Center	
	Dim. A	Dim. B	Dim. C	
1300 kg (3000 lb)	475mm (187 in)	610 mm (24 in)	610 mm (24 in)	A
kg (lb)	mm (in)	mm (in)	mm (in)	

