CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number		
YALE MANUFACTURER	ERP030VT	2013	G807N05223L		
Mast	3 Stage FFL (Triplex)		Hours	4728	
Mast Height Lowered			Voltage	36 Volt	
Mast Height Raised			Attachment	Side Shifter	
Hydraulic Control Valve	3-Function		Directional Control	Lever	
Capacity			Tires	Cushion	
Mast Condition			Stooring Dump Condition		
Mast Comments			Steering Pump Condition Steering Pump Comments		
Lift Cylinder Condition			Hydraulic Pump Condition		
Lift Cylinder Comments			Hydraulic Pump Comments		
Tilt Cylinder Condition Tilt Cylinder Comments			Hydraulic Motor Condition Hydraulic Motor Comments		
Carriage Condition			Control System Condition		
Carriage Comments			Control System Comments		
Load Backrest Condition			Control System Comments		
Load Backrest Comments			Drive Motor Condition		
Forks Condition			Drive Motor Comments		
Forks Comments			Differential Condition		
TORS COMMENTS			Differential Comments		
Overhead Guard Condition			Drive Tires % Remaining	75	
Overhead Guard Comments			Drive Tires % Remaining Drive Tires Condition	75	
Overnead Guard Comments			Steer Tires % Remaining	70	
Seat Condition			Steer Tires Condition	70	
Seat Comments			Steer Axle Condition		
Seat Comments			Steer Axle Condition Steer Axle Comments		
General Appearance Condition			Brakes Condition		
General Appearance Comments			Brakes Comments		
General Appearance Comments			Diakes Confinents		
General Comments			Battery Present	Yes	
			Charger Present	Yes	
			Electrical Condition		
			Electrical Comments		
			_		

Inspector Company Name	Eastern Lift Truck	Inspection Date	7/24/2018 12:00:01 PM	
Inspector Name	jsaum			

IING

ors and Only

perating Tocated or in ors rtment

operating, maintenance cause r death! NITH MAST AND AS SHOWN

Yale

Lift Truck Model ERP030VTN36TE078
Serial No. G807N05223L

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2530 kg (5570 lb) Type E 36 Volts
Truck Wt. Max Battery 3530 kg (7770 lb) Max A.H.(6 Hr Rt) 880

Allowable Battery Wt. 770 kg (1700 lb) to 1000 kg (2200 lb)

Tread Width 890 mm (35.1 in) Back Tilt 5 Degrees

Tire Front Rea

Size 18X7X12-1/8 Cushion 15X4X11-1/4 Dual Cushion

Pressure ---

MAXIMUM	Load Height Dim. A	Dim. B Dim. C		
1360 kg	4450mm	610 mm	610 mm	A
(3000 lb)	(175.2 in)	(24 in)	(24 in)	
kg	mm	mm	mm	1 10
(lb)	(in)	(in)	(in)	













