

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	J30XNT	2013	K160N03318L

Mast	3 Stage FFL (Triplex)	Hours	4922
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity	3000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	30
Overhead Guard Comments		Drive Tires Condition	Chunked
Seat Condition	Damaged	Steer Tires % Remaining	60
Seat Comments	Cushion needs replacement	Steer Tires Condition	
General Appearance Condition		Steer Axle Condition	
General Appearance Comments		Steer Axle Comments	
General Comments		Brakes Condition	
		Brakes Comments	
		Battery Present	Yes
		Charger Present	No
		Electrical Condition	
		Electrical Comments	

1. Backup alarm not working2. Need to replace drive tires (chunked)3. Seat cushion needs to be replaced

Inspector Company Name	Johnny Holguin	Inspection Date	11/25/2018 5:34:09 PM
Inspector Name	szuege		

(* Legend: =Checked OK)











WARNING

Operators and Mechanics Only

Read Operating Manual located on seat or in operators compartment

Failure to follow operating instructions, and maintenance instructions, can cause serious injury or death! CAPACITY WITH MAINTENANCE EQUIPMENT IS SHOWN



Lift Truck Model J30XNT
Serial No. K160N03318L

Attachment: 978 mm (39 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery 2370 kg (5220 lb) Type EO 36 Volts
 Truck Wt. Max Battery 3510 kg (7720 lb) Max A.H.(6 Hr Rt)880
 Allowable Battery Wt. 910 kg (2000 lb) to 1130 kg (2500 lb)
 Tread Width 880 mm (34.9 in) Back Tilt 5 Degrees

Tire Size Front 18X7.8 Solid Rear 15X4.5-8/3.0 Dual Solid

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1360 kg (3000 lb)	4750mm (187 in)	610 mm (24 in)	610 mm (24 in)
kg (lb)	mm (in)	mm (in)	mm (in)

