

# CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E50XN	2013	A268N10264L

Mast	3 Stage FFL (Triplex)	Hours	6624
Mast Height Lowered		Voltage	36 Volt
Mast Height Raised	189	Attachment	Side Shifter
Hydraulic Control Valve	3-Function	Directional Control	Lever
Capacity		Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition		Drive Motor Condition	
Load Backrest Comments		Drive Motor Comments	
Forks Condition		Differential Condition	
Forks Comments		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	90
Overhead Guard Comments		Drive Tires Condition	
Seat Condition		Steer Tires % Remaining	80
Seat Comments		Steer Tires Condition	
General Appearance Condition		Steer Axle Condition	
General Appearance Comments		Steer Axle Comments	
General Comments		Brakes Condition	
		Brakes Comments	
		Battery Present	Yes
		Charger Present	Yes
		Electrical Condition	
		Electrical Comments	

Battery very weak if not dead.

Inspector Company Name	Pape	Inspection Date	12/17/2018 2:58:02 PM
Inspector Name	bemerson		

(\* Legend: =Checked OK)



Lot Track Model E300V-27

Serial No. A268W102640

Attachment: 878 mm (28 1/2 in) to 1200 mm (39 3/8 in) Forks

Track Wt. Less Battery 2270 kg (5020 lb) Type E 24 Volts

Track Wt. Max Battery 4870 kg (10720 lb) Max A. H. 14 m (46 ft)

Allowable Battery Wt. 1940 kg (4280 lb) to 1900 kg (4180 lb)

Forked Width 890 mm (29 1/8 in) Back Tilt 5 Degrees

Tire Front

Rear

Case 25.7 x 1.8 Custom

NEEDLE 3 Custom

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
2150 kg (4730 lb)	4000 mm (131 1/8 in)	650 mm (24 in)	650 mm (24 in)
2100 kg (4620 lb)	4200 mm (137 7/8 in)	650 mm (24 in)	650 mm (24 in)





Hour Capacity 938 A.H.  
Nominal Voltage 36  
Peak Rate 47 Amps  
Specific Gravity 1.275-1.285  
Capacity Weight Stamped on Tray

**HAWKER**  
Part No. PL108152431  
UL CLASSIFIED  
UL

**UniSea**  
10/07/15

**UniSea**  
10/07/15

**HAWKER**  
**POWERLINE**  
PREMIUM POWER

