

CONDITION REPORT - ELECTRIC

Manufacturer	Model	Year	Serial Number
HYSTER COMPANY	E30XN	2013	A269N02195L

Mast	3 Stage FFL (Triplex)	Hours	7995
Mast Height Lowered	82	Voltage	36 Volt
Mast Height Raised	187	Attachment	None
Hydraulic Control Valve	3-Function	Directional Control	
Capacity	3000	Tires	Cushion

Mast Condition		Steering Pump Condition	
Mast Comments		Steering Pump Comments	
Lift Cylinder Condition		Hydraulic Pump Condition	
Lift Cylinder Comments		Hydraulic Pump Comments	
Tilt Cylinder Condition		Hydraulic Motor Condition	
Tilt Cylinder Comments		Hydraulic Motor Comments	
Carriage Condition		Control System Condition	
Carriage Comments		Control System Comments	
Load Backrest Condition			
Load Backrest Comments		Drive Motor Condition	
Forks Condition		Drive Motor Comments	
Forks Comments		Differential Condition	
		Differential Comments	
Overhead Guard Condition		Drive Tires % Remaining	30
Overhead Guard Comments		Drive Tires Condition	
		Steer Tires % Remaining	30
Seat Condition	Damaged	Steer Tires Condition	
Seat Comments	Cushion needs replacement	Steer Axle Condition	
		Steer Axle Comments	
General Appearance Condition		Brakes Condition	
General Appearance Comments		Brakes Comments	

General Comments

1. Seat Cushion needs replacement
2. 30% tread left on drive/steer tires, needs replacement.

Battery Present	Yes
Charger Present	No
Electrical Condition	
Electrical Comments	

Inspector Company Name	Johnny Holguin	Inspection Date	11/25/2018 5:08:30 PM
Inspector Name	szuege		

(* Legend: =Checked OK)



Lift Truck Model **E30XN**

Serial No. **A269N02195L**

Attachment: 907 mm (36 in) SS Crg + 1067 mm (42 in) Forks

Truck Wt. Less Battery **2550 kg (5610 lb)** Type **EO 36 Vc**

Truck Wt. Max Battery **3680 kg (8110 lb)** Max A.H. (6 Hr Rt)

Allowable Battery Wt. **840 kg (1850 lb)** to **1130 kg (2500 lb)**

Tread Width **800 mm (31.8 in)** Back Tilt **5 Degrees**

Tire Front
Size **18X7X12-1/8 Cushion**
Pressure

Rear
15X5X11-1/4 Cushion

MAXIMUM CAPACITY	Load Height Dim. A	Load Center	
		Dim. B	Dim. C
1270 kg (2800 lb)	4750mm (187 in)	610 mm (24 in)	610 mm (24 in)
1310 kg (2900 lb)	4300 mm (169.3 in)	610 mm (24 in)	610 mm (24 in)









